



PCB version pictured

- High current automotive or industrial relays
- Ideal for DC Motor Control and lamps, fans, winch & sunroof motors, vehicle alarms
- Sn Plated, copper terminals for high continuous DC current capacity
- Industry standard Maxi-ISO terminals
- PCB Versions available

ROHS Compliant ✓

Contacts

Contact arrangement	SPST-NO (1 Form A)
Contact material	AgSnO ₂
Max. switching voltage	DC 75VDC - current dependent >24VDC Contact factory
Contact rating (resistive)	70A (14VDC), 20A (24VDC)
Max. switching current (inrush)	make 120A
Rated power	980W
Min. switching current	100mA / 6VDC
Initial contact resistance	≤30mΩ, max. at 0.1A/6VDC (IEC 61810-7 / 4.12)

Coil

Rated voltage	DC 6V, 12V, 24V
Operating range of supply voltage	See coil table 1
Rated power consumption	2.3W (2.5W with resistor)

Insulation

Insulation resistance	100MΩ at 500VDC, 50%RH, 25°C (IEC60255-5 / Item 7)
Dielectric strength	coil to contact 500Vrms / 1 min (IEC 60255-5 Item 6)
	contact to contact 500Vrms / 1 min (IEC 60255-5 Item 6)

General Data

Operating time	ms ≤7
Release time	ms ≤5
Electrical life	ops. 1 x 10 ⁵ (IEC61810-7 / Item 4.30)
Mechanical life	ops. 1 x 10 ⁷ (IEC61810-7 / Item 4.31)

Environmental

Environmental protection	IP54 Dust cover, IP67 Fully sealed (optional)
Ambient temperature	operating -40 to 125°C (Derate above 85°C - consult factory)
	storage -40 to 155°C
Shock resistance	functional 30m/s ² 6ms
	destructive 196m/s ² (20g)
Vibration resistance	DA 1.8mm, 20 to 500Hz
Dimensions	L x W x H 26.5 x 26.5 x 25.2mm (excluding terminals)
Weight	approx. 36g depending on style and mounting

Ordering Code

D G 5 6 C - 7 0 2 1 - 7 5 - 1 0 2 4 - D R

Series C = 70A

High current

Coil code:

See table 1

Contact material

70: AgSnO₂

Contact configuration

21: SPST-NO

(1N/O, 1 Form A)

Environmental protection

7: Dust cover IP54

9: Dust cover with plastic mounting bracket

Mounting & terminations

5: For PCB

6: Flat blades

Coil options

Blank: No options

R: Parallel resistor

D: Parallel diode +85, -86

DR: Parallel diode -85, +86 (standard for diode)

DD: Double diodes +86 (see fig. 2 for detail)

